

NP-ACSM

Matched Pair Acetylene Pellistor Gas Sensor

053350 rev.1 dated 06/10/2021



Key Features

The N.E.T. NP-ACSM is a catalytic (pellistor) type flammable gas sensor supplied as a matched pair of elements mounted on TO4 size headers and protected by a metal can. The matched pair sensor is mounted in a plastic housing of standard diameter of 32 mm (see figure).

The sensor detects and measures the presence of flammable gases and vapours in air, in the range 0-100% of the Lower Explosive Limit (LEL) of the gas or vapour being measured. Designed as a sensing platform for use in fixed flammable gas detection systems, the NP-ACSM exhibits excellent long term zero and sensitivity stability and a high level of resistance to catalytic poisons. The device is compatible with a wide range of commercially available Gas Detection Systems and remote flammable gas detection heads.

The highly automated manufacturing procedure employed results in a

NET Catalytic Bead Pellistors

Our Pellistor, or catalytic bead sensor, line is selected by N.E.T. and manufactured, on OEM basis, by world's best manufacturers.

The sensor monitors the presence of a combustible gas or vapor in air (or atmospheres containing oxygen) up to the Lower Explosive Limit (LEL). A Pellistor operates on the principle that when a combustible gas/air mixture is in contact with the catalyst surface, maintained at about 500°C as current is passed through it in a Platinum coil, combustion occurs. The heat generated increases the temperature of the bead, which in turn changes the resistance of the coil. The resistive signal change produced is proportional to the gas concentration and can be measured by using the coil as a temperature thermometer in a standard Wheatstone bridge circuit.

Given Pellistors capacity to ignite flammable gas mixtures, is typically necessary to encapsulate the beads in a certified flameproof enclosure, such as N.E.T. Certified


Heads. This will allow the beads to be exposed to the target gas without the risk of ignition.

Pellistors are an inexpensive and effective solution to monitor Methane (CH₄) and other Hydrocarbons and, generally, combustible gases such as Hydrogen (H₂) and Ammonia (NH₃). They offer very low humidity and temperature dependence.

As their measurement principle is based on combustion, Pellistors cannot be used in inert atmospheres and require the presence of Oxygen. Additionally, they are susceptible to inhibition and poisoning by chemicals such as Lead- and Sulphur-containing compounds, phosphates and organic silicones. In case any of those two risks are present, try our InfraRed sensors.

The standard dimensions and the electrical output make our Pellistor perfectly compatible with a wide range of commercially available Gas Detection Systems and remote flammable gas detector heads.


Mechanical specifications



Product specifications

Technical Specifications	Recommended Voltage:	2.0V +/- 0.1V
	Current Drawn:	150 +/- 10mA
	Zero Offset:	0mV +/- 25mV
	Sensitivity:	45 mV/%vol Acetylene
	Range:	0-100% LEL
	Linearity:	Effectively Linear to 50% LEL
	Accuracy:	+/- 500ppm
	Maximum Long Term Drift (Span):	< +/- 1% LEL/Month
	Maximum Long Term Drift (Zero):	< +/- 0.5 mV/Month
	Response Time:	T50: 3 sec T90: 8 sec
Operating conditions	Operating Temperature:	-20°C to + 70°C
	Temperature Drift (Zero): (-20°C to +70°C)	< +/- 2% LEL
	Operating Humidity:	0-195% RH, non-condensing
	Humidity Response:	+/- 2% LEL

Recommended circuit



Warranty and warning

Use within specified conditions.

Sensor characteristics must be measured in clean air without noise gases.

Electrode pins must be correctly connected. Wrong connection does not allow correct functions.

Do not apply voltage directly to electrode pins.

Do not bend pins.

Do not solder to electrode pins directly. Use exclusive sockets.

Do not use contact grease on electrode pins.

Do not put excess strength on electrode pins.

If sensor housing is damaged or scratched, do not use sensor.

Do not blow organic solvents, paints, chemical agents, oils, or high concentration gases onto sensor.

Do not disassemble or change any parts.

If sensor is used under irregular atmosphere, contact us for assistance.



N.E.T. has a policy of continuous development and improvement of its products. As such the specification for the device outlined in the data sheet may be changed without notice. In case of modification of the product, N.E.T. disclaims all liability.

No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of N.E.T. For permission requests or technical support please contact or write to the address below:

N.E.T. SRL

Via Legnano, 2 | 20010 | Cornaredo | Milano | Italy

T +39.02.9354.4190

E info@nenvitech.com